

(19) World Intellectual Property  
Organization  
International Bureau



(43) International Publication Date  
12 May 2005 (12.05.2005)

PCT

(10) International Publication Number  
**WO 2005/042277 A3**

(51) International Patent Classification<sup>7</sup>: **B60C 29/06**

(21) International Application Number:  
PCT/DK2004/000763

(22) International Filing Date:  
4 November 2004 (04.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
PA 2003 01640 4 November 2003 (04.11.2003) DK

(71) Applicant (for all designated States except US): **OPFIND-ERFABRIKKEN APS** [DK/DK]; C/O Søren Badstue, Skodsborgparken 32, 4th, DK-2942 Skodsborg (DK).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **BADSTUE, Søren** [DK/DK]; Sodsborgparken 32, 4th, DK-2942 Skodsborg (DK).

(74) Agent: **INSPICOS A/S**; Bøge Allé 5, Postboks 45, DK-2970 Hørsholm (DK).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


**Published:**

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:  
9 June 2005

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A PRESSURE RELIEF DEVICE FOR AIN INFLATABLE TIRE



(57) Abstract: A pressure relief device (100; 200; 300; 400; 400) for an inflatable tire comprises a body (102; 202; 302; 402; 502) having a chamber (124; 228; 324; 424; 524) with an inflation valve arranged in the body. An overpressure valve in the body releases air when the air pressure in the chamber exceeds a predetermined threshold pressure level. The overpressure valve includes at least one air conduit (128; 228; 328; 428; 528) extending from the chamber through the body in order to provide a passage to a surrounding atmosphere. A ring-shaped resilient member (130; 230; 330; 420; 530) is contractively fitted around an outer surface portion of the body, so as to keep the air conduit in a normally closed state. The properties and dimension of the resilient member are such that it is stretched when the air pressure in the chamber exceeds the predetermined pressure level, so as to provide an air passage from the conduit to the surrounding atmosphere. A plurality of pressure relief devices may be included in a kit, wherein the devices define different predetermined pressure levels.